



## **NEW CONFIGURATION**



## **MIURA WALLPAPER**

## AUTOMATIC XY CUTTER FOR WALL PAPER

Highly precise cutting machine for X and Y trimming with automatic vertical cutting correction.

Suitable for wallpaper and many other flexible supports.

- HIGH PRODUCTIVITY
  - Combined horizontal and vertical cutting for the fastest finish of your rolls
- **MAXIMUM CUTTING PRECISION**

The edge control guarantees perfect joints of pattern and designs on the wall.

The sensor has a reading accuracy of 0,05 mm

**NO WASTE OF MATERIAL** 

Each lengthwise rotary crush cutter includes a fine positioning of the cutting blades for micro-adjustments. The result is a perfectly cut wallpaper

**MAITENANCE COSTS** 

Miura ensures low costs maintenance. Blade replacement is simple and needs just a few minutes

**LONG-TERM RELIABILITY AND SAFETY** 

The lengthwise rotary crush cutters last for 100's of thousands of cuts and are safe for the operator

**TOUCH SCREEN DISPLAY** 

Intuitive set up of the cut parameters

**CUTTING FLEXIBILITY** 

3 cutting modes: 1. automatic by crop marks; 2. sheeting; 3. manual: Miura can trim different lenghts from the same printed roll


**SMART REMOTE SYSTEM** 

Miura can be connected to the internet network for remote assistance, for fast and efficient diagnostics





Advanced cutting mark reader



Optical sensor for vertical alignment



Automatic vertical alignment control panel



User-friendly software design



Fine positioning of the cutting blades (standard)



Can be fitted with: (optional):


- 1. **Motorized Stacker** in line with the cutter: height and inclination electronically adjustable; extensible length up to 3,2 meters
- 2. Folding collecting table
- 3. Tiltable collecting table with wheels



Fine pressure adjustment (according to the types of material)



Single lengthwise rotary crush cutter (twin cutters optional)



Front rewinding system: it rewinds the cut media up to three smaller rolls (optional)



Slimline lengthwise rotary crush cutter, single or twin, (optional)

Working width	1650 mm (65 in)
Feeding speed	1 - 30 m/min (3 - 98 ft./min)
Usable lengthwise cutting units	max. 8
Cross cutting speed	5 - 120 m/min (16 -393 ft/min)
Max. roll diameter	Ø 300 mm (12 in)
Max. roll weight	60 kg (132 lbs)
Suitable materials	Wallpaper, Canvas & polyester (with liner), paper, vinyl & self adhesive vinyl, backlit & frontlit display, PVC banner, magnetic rubber, polycarbonate (film), reflective material, many more
Power supply	230 V - 50 Hz - 650 W
Dimensions (W x L x H)	2460 x 1000 x 1330 mm (96 x 39 x 52 in)
Weight	415 kg (881 lbs)
Packing Dimensions (W x L x H)	2650 x 1150 x 1650 mm (104 x 45 x 65 in)
Packing Weight	500 kg (1102 lbs)

Manufactured in compliance with CE regulations



## Follow us:















100% Made in Italy

www.flexa.it

